



## PRISLISTA SVARTPLÅT GIROVENT AB Maj 2019 Ordinarie/Äta

Grupp	1	2	3	4	5
Största sida i cm	30	80	140	200	240
Plåttjocklek i mm	1,5	1,5	1,5	1,5	1,5
Kr/m2 Galv	856	856	856	856	856
<b>Rostfritt 2017:-/m2 Inga FFE</b>					
<b>Antal FFE a 122:-/st</b>					
Detalj	FFE	FFE	FFE	FFE	FFE
T-stycke	6	6	9	14	22
Böj valfri vinkel	3	3	6	8	11
Böj valfri vinkel Rund Ytter	6	6	12	16	22
Dim1+A1	3	3	6	8	11
Dim 2-3-4-5+A2	4	4	8	11	16
Dim special	7	7	15	17,5	22,5
Övergång2-3-4-5	7	7	13,5	16	20
Övergång Special	9	9	19,5	23	29
Avstick Cirkulärt	3	3	6	10	14
S-Böj	4	4	8	11	16
Gavel	1	1	2	3	4
Mont.avstick,rensl.=DM	3	4	6	7	8
Kanaler ej Standardlängd	2	2	3	4	5
Standardlängd 1250,2000	0	0	0	0	0

<b>Isolering</b>	CB3 = EI 15 Brandcleantec 30mm	<b>792</b>			
	CB7 = EI 30 Brandcleantec 70mm	<b>895</b>			
	CB12=EI 60 Brandcleantec 120mm	<b>1127</b>			
	CG2 Cleantec 20mm	<b>527</b>			
	CG3 Cleantec 30mm	<b>561</b>			
	CG5 Cleantec 50mm	<b>605</b>			
	CG10 Cleantec 100mm	<b>791</b>			
	Ytskydd perforerad plåt	<b>589</b>			
	Reperationstape Cleantec + 50mmx50m	<b>470 Netto</b>			
	<b>FFE-Tillägg för isolering per detalj och kanal</b>				
<b>Grupp</b>					
	<b>1</b>	<b>2</b>	<b>3</b>	<b>4</b>	<b>5</b>
	1,5	3	4,5	6	7,5

Renslucka största sida	Renslucka oisolerad	Renslucka Isolerad
300	11 FFE	15 FFE
400	12 FFE	16 FFE
500	13 FFE	18 FFE
600	16 FFE	20 FFE
700	18 FFE	23 FFE
800	20 FFE	26 FFE